

# FL

CATEGORY & CAPACITY  
**ASEPTIC**  
 ◇ CORE



DESCRIPTION	DATA
MECHANICAL SPEED (Bpm)	From 100 to 500 bottles/min.
FILLING RANGE (Standard)	From 10 ml. to 300 ml.
EXTRA (Min and max)	From 2 ml to 1000 ml.
DOSAGE ACCURACY	Between +/-0,5% and +/- 2% volume
SINGLE DOSAGE & MULTIPLE DOSAGE	Yes
BOTTLES RANGE (Standard)	From Ø 14 to Ø 32 mm. x height from 30 to 80 mm
EXTRA	Min. Ø 8 mm. to max. height 220 mm.
FILLING SYSTEMS	Piston pumps (syringes), peristaltic pumps, flowmeter and mass dosators
MOTION SYSTEMS	Continuous motion, combined motion (continuous + intermittent)
FEEDING SYSTEM	Full automatic
CAN WORK IN STERILE ROOMS	Standard
LAMINAR FLOW EQUIPPED	Option
OPEN & CLOSED RABS EQUIPPED	Option
CIP/SIP EQUIPPED	Option
ELECTRONIC FILLING ADJUSTMENT	Yes
AUTOMATIC REJECT	Yes
NO BOTTLE NO FILL NO CAP	Standard
100% IPC NET WEIGHT CONTROL	Option